





ELEMENT SPECS					
PART NUMBER	235P				
MATERIAL	POLYESTER				
FLOW RATE	570 CFM	968 m³/hr			
SURFACE AREA	9.4 ft ²	0.9 m ²			
I.D.	4.75"	121mm			
O.D.	7.88"	200mm			
HEIGHT	9.47"	241mm			

FINISH: GRAY POWDER

	SOLBERG® iltration • Separation • Silencing 30.773.1363 • www.solbergmfg.com
--	--

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS EUDINISHED. IT WILL BE DETURNED LIDON DEFOLIEST. WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL NUMBER: FT-235P-301	MODEL NUMBER: ET-235P-301		SHEET:
		1 OF 2	

MATERIAL: CARBON STEEL

DESCRIPTION: FT-235P-301, GRAY

MODEL #: FT-235P-301

REV: APPROVED BY: PROJECT: DRAWN BY: WZL Α **DATE:** 1/23/2020 DATE: