





THE INFORMATION CONTAINED HEREIN'IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGI UPON PRODUCTION.

UNLESS OTHERWISE SPECIFIED: -DIMENSIONS ARE IN INCHES -REF: APPROXIMATE DIMENSIONS, NO TOLERANCES API -FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER



		ELEMENT SPECS						
		PART NUMBER		375P				
			MATERIAL	Polyester				
		FLOW RATE		1500 CFM	2549 m³/hr			
		SURFACE AREA		28.0 ft ²	2.6 m ²			
			I.D.		8.00"	203mm		
		O.D.		11.75"	298mm			
			HEIGHT		14.50"	368	nm	
	MODEL #: CSL-375P-601	MAT	ERIAL: CARBON STEEL	FINISH: BLACK POWDER				
	MODEL NUMBER: CSL-375P-601					SHE		
~-					1 OF 1			
θE	DESCRIPTION: CSL-375P-601, BLACK							
APPLY	PROJECT:	DR	AWN BY: DDH		APPROVED BY:	JEB		REV:
R		DAT	TE: 10/4/2019		DATE: 10/4/2019			