

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL

AND THE PROPERTY OF SOLBERG MANUFACTURING INC.
AND IT IS FURNISHED TO YOU WITH THE EXPRESS


UNDERSTANDING THAT IT WILL NOT BE REPRODUCED,

COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR

USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT

WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE

RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.





ELEMENT SPECS		
PART NUMBER	345P	
MATERIAL	Polyester	
FLOW RATE	1100 CFM	1869 m³/hr
SURFACE AREA	22.1 ft ²	2.1 m ²
I.D.	6.00"	152mm
O.D.	9.75"	248mm
HEIGHT	14.50"	368mm

SHEET:

1 OF 1

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

FINISH: BLACK POWDER MODEL #: CSL-345P-501 MATERIAL: CARBON STEEL

DESCRIPTION: CSL-345P-501, BLACK

MODEL NUMBER: CSL-345P-501

APPROVED BY: M.C. REV: **PROJECT: DRAWN BY:** CRW SD15877 В **DATE:** 8/2/2010 **DATE:** 8/2/2010



SOLBERG® Filtration • Separation • Silencing 630.773.1363 • www.solbergmfg.com