





ELEMENT SPECS				
PART NUMBER	15P			
MATERIAL	Polyester			
FLOW RATE	35 CFM	59 m³/hr		
SURFACE AREA	0.5 ft ²	0.1 m ²		
I.D.	SEE DRAWING			
O.D.	SEE DRAWING			
HEIGHT	SEE DRAWING			
-				

4=4	SOI BERG®
smi	JOLDLING
	Filtration • Separation • Silencing 630.773.1363 • www.solbergmfg.com

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER ANY OTHER RESTRICTIONS WHICH MAY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY.
ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL NUMBER: 15P	5D	SHEET:
WODEL NOWBER.	51	1 OF 1

DESCRIPTION: 15P, POLY

PROJECT:	DRAWN BY: NAS	APPROVED BY: NAD	REV:
	DATE : 6/24/2019	DATE : 6/24/2019	