







## **NOTES & SPECIFICATIONS:**

- 1. FLANGES TO BE PROTECTED DURING PRODUCTION & SHIPMENT.
- 2. UNIT TO BE HELIUM LEAK TESTED TO 1 x 10-5 mbar L/s.

ELEMENT SPECS				
PART NUMBER	850			
MATERIAL	PAPER			
FLOW RATE	290 CFM	493 m³/hr		
SURFACE AREA	13.1 ft²	1.2 m <sup>2</sup>		
I.D.	3.50"	89mm		
O.D.	5.88"	149mm		
HEIGHT	8.69"	221mm		

FINISH: BLACK POWDER

SOLBERG® Filtration \* Separation \* Silencing 630.773.1363 • www.solbergmfg.com

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE RESTRICTION IS IN ADDITION TO, AND DOES NOT IN ANY WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

## **TOLERANCES**

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.** 

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

	CUEET.
MODEL NUMBER: WL-850-K63B	SHEET:
	1 OF 2

MATERIAL: CARBON STEEL

**DESCRIPTION:** WL-850-K63B, BLACK

PROJECT:	DRAWN BY: TAS	APPROVED BY: EZR	REV
	<b>DATE</b> : 7/10/2019	<b>DATE</b> : 7/10/2019	Α