







NOTES & SPECIFICATIONS:



1. UNIT RATED FOR 200 - 450 SCFM (340-765 m³/hr).

REV:

В



THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF SOLBERG MANUFACTURING INC. AND IT IS FURNISHED TO YOU WITH THE EXPRESS UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED IN ANY MANNER, LOANED OR OTHERWISE TRANSFERRED TO OTHERS ENTIRELY OR IN PART, NOR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT WAS FURNISHED. IT WILL BE RETURNED UPON REQUEST TO SOLBERG MANUFACTURING INC. THE ABOVE WAY ALTER, ANY OTHER RESTRICTIONS WHICH MAY APPLY TO THE INFORMATION CONTAINED HEREIN.

TOLERANCES

DIMENSIONS ARE FOR REFERENCE ONLY. ALL DIMENSIONS ARE SUBJECT TO CHANGE **UPON PRODUCTION.**

UNLESS OTHERWISE SPECIFIED:
-DIMENSIONS ARE IN INCHES
-REF: APPROXIMATE DIMENSIONS, NO TOLERANCES APPLY
-FINISH: BREAK EDGES TO .005-.020 RADIUS/CHAMFER

MODEL #: ST-SML445-301C	MATERIAL: CAST ALUMINUM/PLASTIC	FINISH: NONE	
MODEL NUMBER: ST-SML445-301C			SHEET: 1 OF 1
DECODIDETION OF CMI 445 0040 OLI			

| DESCRIPTION: ST-SML445-301C, CLEAR BUCKET

PROJECT:	DRAWN BY: DDH	APPROVED BY: CRW
	DATE : 4/29/2015	DATE : 4/29/2015